

Product Name	Working Dimensions	Feed/Operation		Clamp Pressure			Manufacturer's Comments
		Manual	Automatic	Pneumatic	Hydraulic	Electric	
<b>Biesse Group America Inc., P.O. Box 19849, Charlotte, NC 28219-9849 Tel: (704) 357-3131 Fax: (704) 357-3130</b>							
Cosmo NK	W max 700, H 300-1300mm, L 300-2500mm	■				2698 lbs	Easy to use manual clamp
Performer TP	W 180-1000mm, H 250-1300mm, L 250-2950mm		■		V: 4271 H: 3596 lbs		Self-setting automatic throughfeed case clamp
<b>Delmac Machinery Group, 4322 Piedmont Parkway, Greensboro, NC 27410 Tel: (336) 854-1211 Fax: (336) 854-0811 delmac.com</b>							
Bonacin Closer N2500F	Max/Min 98.4"/7.9" H 49.2"/7.9" D 25.6"			Semi-Auto Front Load		Adj. by inverter	Allows overlapping top/bottom panel or moulding, very quiet, adjustable pressure
Bonacin Closer P2500T	Max/Min 98.4"/7.9" H 49.2"/7.9" D 25.6"			Auto, Thru Feed		Adj. by inverter	Same as above
CPC PAM 3LF	Max/Min 90.6"/25.6" H 43.3"/9.0" D 25.6"			Auto, Front Load		Adj. by regulator	Heavy steel frame, self-centering clamp design
CPC SAP 3ARM	Max/Min 98.4"/15.7" H 43.3"/1128" D 25.6"			Auto, Thru Feed		Adj. by regulator	Heavy steel frame, two movable beams for fast changeovers, automatic positioning
<b>Hess Group America, Inc., P.O. Box 537, Point Pleasant, NJ 08742 Tel: (800) 973-4377 or (732) 892-3558 Fax: (732) 295-3753</b>							
Laura	98.4" x 49.2" x 24"	■			■		Quick changeover, clamping corners automatically reposition when changing opening size
<b>Italpresse USA Inc., 26520 Mallard Way, Punta Gorda, FL 33950 Tel: (888) 743-8505 Fax: (941) 639-1663</b>							
SP/1-A	Length: max. 98", min. 12" Height: max. 48", min. 12" Width: max. 27.5", min. 10"						Electronic control; auto reading of cabinet sizes; through-feed operation; fully auto
Primatist/25A	Length: max. 98", min. 10" Height: max. 49", min. 9" Width: max. 25"						Full automatic operation; manual loading
<b>Ritter Mfg. Inc., 1300-B W. 4th St., Antioch, CA 94509 Tel: (925) 757-7296 Fax: (925) 757-7083</b>							
R-525	50" x 100"	■				■	Semi /auto feed
R-525 DE	2 @ 50" x 50" or 1 @ 50" x 100"	■				■	Semi /auto feed; Double-end
<b>Stiles Machinery Inc., 3965 44th St. S.E., Grand Rapids, MI 49512 Tel: (616) 698-7500 Fax: (616) 698-9411 stilesmachinery.com</b>							
Ligmatech MPH 100	2500 x 1220mm, depth 600 or 800mm	■		■			Easy to adjust
Ligmatech MPH 400	2500 x 1400mm, depth 800 or 900mm	■				■	Infin. adj., does not require pressure pads
Ligmatech MDE 110	1500mm, 2800mm, and 3000mm available: height 1320mm; depth 800 or 1000mm.			■		■	Throughfeed clamp; automatically adjusts to case size; edge aligned (not center aligned) during clamping cycle
Ligmatech MDE 160	1500mm, 2800mm, and 3000mm available: height 1320mm; depth 800 or 1000mm.			■		■	Throughfeed clamp; automatically adjusts to case size; edge aligned (not center aligned) during clamping cycle; automatic back nailing device
<b>Tritec Associates Inc., 45714 Oakbrook Ct., Unit 140, Sterling, VA 20166 Tel: (703) 904-7890 Fax: (703) 904-7889</b>							
Gannomat Concept Easy 70	2000 x 2100/2900 x 700 mm	■				■	Automatically adjusts to case size
Gannomat Concept Primus70	2550 x 1400 x 700 mm	■		■		■	Automatically adjusts to case size
Gannomat Concept Primus 90	2550 x 1400 x 900 mm	■		■		■	Automatically adjusts to case size
Gannomat Concept ECO 70	2550 x 1400 x 700 mm	■				■	Automatically adjusts to case size
<b>J.C. Uhling Products, P.O. Box 445, Cottonwood, ID 83522 Tel: (208) 962-3271</b>							
HP 5000	100" x 24" x 50"	■		■		■	Clamps all case goods incl. custom req
HP 4000	100" x 24" x 50"	■				■	Clamps all case goods incl. custom req
HP 3000	55" x 24" x 96"	■				■	Clamps all case goods incl. custom req
HP 2000	50" x 24" x 46"	■				■	Clamps all case goods incl. custom req
<b>Warsaw Machinery Inc., 610 S. Detroit St., Warsaw, IN 46580 Tel: (574) 267-5355 Fax: (574) 267-5366</b>							
Handy Model 630-4	48"x36"x36"	■					Air pod. Options: secondary clamping, power traverse, adj. to 8000 lbs w/ main jaws
Handy Model 630-6	72"x36"x36"	■			same		See above
Handy Model 630-8	96"x36"x36"	■			same		See above
Handy 123/124 Econo Clamp	48"x48" 48"x49"	■			5000 main 2500 sec		Power traverse optional 123 - one way, 124 - two way
Handy 97/960 Heavy Frame Clamps	48"x160" 60"x168"	■			16000 main 2500 sec.		Power traverse optional 970 - one way, 960 - two way