

Brand Name and/or No.	Type	Manual	Auto.	Belt Speed	No. of Heads	Application	Characteristics
AWED, 1175 Buford Hwy., Ste. 101, Suwanee, GA 30024 Tel: (770) 831-9800 Fax: (770) 831-7404							
13	Bermaq						Shape and sand. Multiple stations.
12	Bermaq						Shape, sand and hot stamp foiler.
Adwood Corp., P.O. Box 1195, High Point, NC 27261 Tel: (336) 884-1846 Fax: (336) 841-6493							
Bulldog Brisk Series	2		■	Variable	Up to 3	LBP, VP, P, FF	Solids, veneer.
Bulldog Series	2		■	Variable	Up to 3	LBP, VP, P, FF, O	Constant passline.
Maxx Series	2		■	Variable	Up to 4	LBP, VP, P, FF, O	Planer, roller, Combi, segmented pad.
Atlantic Machinery Corp., 36 South End Plaza, New Milford, CT 06776 Tel: (860) 354-7200 Fax: (860) 354-0315							
Bini Export 2500	4	■		70 fps	1	LBP, VP, FF	Belt stroke sander.
ACM OBS 150	5		Semi	24-35 fpm	1	LBP, VP, FF, O	Combined edge sanding machine with oscillation belt system.
LASM NTS 150	5		Semi	15-60 fpm	1	LBP, VPP, FF, O	Combined edge sanding machine with oscillation belt system.
LASM Shaper/Profile/Sander				0-66 fpm	Up to 7	LBP, VP, FF, O	One variable speed (1-7500 rpm, 360° tilting station for sanding and shaping). One sanding belt station with 135° of tilt and 3/4" vertical oscillation.
Paoloni Kalibra 10	2		■	Multiple	1-2	LBP, VP, FF	Combination head.
Paoloni Kalibra 20	2		■	Multiple	1-2	LBP, VP, FF	Combination head.
Paoloni Kalibra 30	2		■	Multiple	1-2	LBP, VP, FF	Combination head.
Paoloni Kalibra 40	2		■	Multiple	1-2	LBP, VP, FF	Combination head.
Paoloni Kalibra 50	2		■	Multiple	1-2	LBP, VP, FF	Combination head.
Biesse America, P.O. Box 19849 Charlotte, NC 28219-9849 Tel: (704) 357-3131 Fax: (704) 357-3130							
BIESSESAND LEVIA 200 Series	2	■		Var. 3.5-18 m/sec	1 or 2 units	SW, veneer	37" wide table
BIESSESAND LEVIA 300 Series	2	■	■	Var. 3.5-22 m/sec	1, 2 or 3 units	SW, veneer	43" or 53" wide table
BIESSESAND REGAL 300 Series	1,2,12	■	■	Var. 3.5-22 m/sec	1, 2 or 3 units	SW, veneer, custom configured, knife flasher, flexible veneer, sealer application	43" or 53" wide table
BIESSESAND REGAL 500 Series	1,2,12	■	■	Var. 3.5-22 m/sec	1, 2, 3 or 4 units	SW, veneer, custom configured, knife flasher, flexible veneer, sealer application	53" wide table
BIESSESAND REGAL 800 Series	1,2,12	■	■	Var. 3.5-24 m/sec	1-6 units	SW, veneer, custom configured, knife flasher, flexible veneer, sealer application	53" wide table
Cantek America Inc., PMB #104, 1124 Fir Ave., Blaine, WA 98230 Tel: (888) 982-2683 Fax: (604) 540-1780							
C251	2		■	Fixed	1	LBP, FF	Combination head, power table rise/fall, variable feed speed.
C371	2		■	Fixed	1	LBP, FF	Combination head, power table rise/fall, variable feed speed.
C372	2		■	Fixed	2	LBP, FF	Drum, combination head, digital thickness control, variable feed speed.
PR-Series	2		■	Variable Optional	Up to 4	LBP, FF	Can be configured with 1-4 heads, digital thickness control, inverter feed, air jet belt cleaners, vacuum bed.
PR-NDA	12		■	Variable Optional	Up to 4	LBP, FF	Spiral insert knife planer with up to 3 sanding heads.
GS48/GD60D	5	■		Fixed	1	LBP, FF	Oscillating edge sander with single/double sided capacity, 9" wide belt.
Cefla Finishing Group, 6125 Harris Technology Blvd., Charlotte, NC 28269 Tel: (877) 233-5240							
Dimac Profitech Series	13		■	Up to 200 fpm	Up to 8	LBP, VP, P, FF, MDF	Profile sander for mouldings, linear components. Abrasive wheels and/or brushes used as sanding medium. Maximum part width 8".
Dimac Profitech Plus Series	13		■	Up to 225 fpm	Per customer requirements	LBP, VP, P, FF, MDF	Profile sander for mouldings, linear components. Abrasive belts, wheels, and/or brushes used as sanding medium. Belts can be flat or shaped for profile. Maximum part width 8".
Dimac Brusstech Series	10		■	Up to 150 fpm	Up to 6	LBP, VP, P, FF, MDF	Profile brush/denibber for mouldings, linear components. Abrasive brushes used as sanding medium. Recommended for white wood & between coat brushing/denibbing. Maximum part width 12" with proper configuration.
Sorbini Smartedge Edgesander	5		■	Up to 100 fpm	Per customer requirements	LBP, VP, P, FF, MDF	Single-sided edge sanding and/or prep. of flat panels. Abrasive belts, wheels and/or brushes used as sanding medium. Shaping/milling stations avail. Max part thick. 3"
Sorbini VS Series	10		■	Variable	Up to 4	LBP, VP, P, FF, MDF	Brushing/denibbing of flat panels, raised panel doors & linear components. Top & bottom brushing/denibbing avail. Tampico, Tynex, Edrulfex & horsehair used as medium.
Sorbini Smartsand Series	10		■	Variable	6 drums	LBP, VP, P, FF, MDF	Brushing/denibbing of flat panels, raised panel doors and linear components. Top side brushing/denibbing only. Accepts specific brushing media.
Costa & Grissom Machinery Co. Inc., 107 Seminole Drive., P.O. Box 4589, Archdale, NC 27263 Tel: (336) 434-6644 Fax: (336) 434-6656							
Costa Series A	1,2,12		■	var. 0-66 fps	1-3	LBP,VP,FF,O	Entry level. Solids, veneers, sealers. Sectioned pads, floating feed table, var. cut speeds.
Costa Series AW	2,12		■	3600 rpm	1-3	LBFO	Entry level knife planer/sander. Automatic slow down on feed speed.
Costa Series SA	1,2,12		■	var. 0-66 fps	1-3	VP,FF,O	Entry level. Solids, veneers, sealers. Sectioned pads, floating table, passline height.
Costa Series KAW	2,12		■	3600 rpm	1-3	LBFO	Entry level knife planer/sander. Passline height. Automatic slow down on feed speed.
Costa Series KKA	1,2,12		■	var. 0-66 fps	2-6	VP,FF,O	Entry level bottom + top calibrator.
Costa Series S	1,2,12		■	var. 0-99 fps	1-5	VP,FF,O	Solids, veneers, lacquers, sealers. Sectioned pads, floating feed table, chevron belts, variable cutting speeds, 128' belts. PC control.
Costa Series K	1,2,12		■	var. 0-99 fps	1-6	LB,VP,PP,FF,O,W	Top calibrating machines.
APPLICATION: LBP = Lumber & Basic Products VP = Veneer & Plywood P = Particleboard FF = Furniture & Fixtures O = Other W = Waferboard							
TYPE CODE: Numbers in "Type" column are keyed to use descriptions below 1. Abrasive Planer 3. Drum 5. Edge Sander 7. Open Drum 9. Spool 11. Disc 13. Profile/Custom Sanding 2. Widebelt 4. Stroke Type 6. Pneumatic Drum 8. Vertical Belt 10. Brush 12. Other 14. Sander for Curved/Irregular Pieces							

SANDING & FINISHING

Brand Name and/or No.	Type	Manual	Auto.	Belt Speed	No. of Heads	Application	Characteristics
Costa & Grissom Machinery Co. Inc., 107 Seminole Drive., P.O. Box 4589, Archdale, NC 27263 Tel: (336) 434-6644 Continued							
Costa Series KB	1,2,12		■	var. 0-99 fps	1-4	LB,FV,PP,FF,O,W	Bottom calibrating machines.
Costa Series KK	1,2,12		■	var. 0-99 fps	2-10	LB,FV,PP,FF,O,W	Bottom + top calibrating machines.
Costa Series KHV	2		■	var. 0-99 fps	1-5	VP,FF,O	Veneer, flexible veneer, edge banding sander. Widths from 14" to 52".
Costa Series K9	1,2,12		■	var. 0-99 fps	1-5	LB,FV,PP,FF,O,W	Top calibrating machines. High speed applications. Modular construction. Working widths from 53" to 86". Feed speeds up to 300 fpm. PC control.
Costa Series K95	1,2,12		■	var. 0-99 fps	1-4	LB,FV,PP,FF,O,W	Bottom calibrating machines. High speed applications. Modular construction. Working widths from 53" to 86". Feed speeds up to 300 fpm. PC control.
Costa Series KW	2,12		■	7200 rpm	1-6	LB,F,O	Knife planer/sander. Automatic slow down on feed speed. High speed operation
Costa Series BC	10		■	var. 0-200 rpm	1-3	VP,FF,O,W	Brush cleaning machines. Stand alone or line insertion.
Costa Series GB	12,13		■	var. 0-99 fps	1-5	LB,F,O	Grain highlighting machines. Stand alone or line insertion.
Costa Series BF	10,12,13		■	var. 0-200 rpm	2-4	VP,FF,O,W	Denibbing machines. Stand alone or line insertion.
Costa Series XGS	2,12,13		■	var. 0-99 fps	1-4	LB,FF,O	Cross grain scratch removal machine.
DPI - Advanced Finishing Technologies, 2241 Lake St., Niles, MI 49120 Tel: (269) 684-2259 Fax: (269) 684-2261							
DeStefani	5		■	Variable	1-10+	LBP,VP,P,FF,O,W	Edge sanding of panels, belt and/or wheel sanding heads.
DeStefani	12		■	Variable	2 + 4	LBP,VP,P,FF,O,W	Shape and sand, 1-2 shapers, combo wheel and belt sanding heads.
DeStefani	13		■	Variable	1-10+	LBP,VP,P,FF,O,W	Profile sander for mouldings, wheel and/or belt sanding heads.
DPI Denibber	13		■	Variable	1-6	LBP,VP,P,FF,O,W	Denibb profiles with loose sandpaper wheels.
DPI Widebelt	2		■	Variable	1-3	LBP,VP,P,FF,O,W	Widebelt sander for flat panels, 37"-51"
DPI Denibber	12		■	Variable	1-4	LBP,VP,P,FF,O,W	Denibb panels with loose sandpaper wheels.
DPI Brush	12		■	Variable	1-2	LBP,VP,P,FF,O,W	Panel cleaner after sanding.
DV-Systems, 6031 Harris Technology Blvd., Charlotte, NC 28269 Tel: (704) 598-0020 Fax: (704) 598-3950							
SPL/4	13		■	500-3000 rpm	4	VP,P,FF,O	Profile sander with abrasive wheels.
SPL/6	13		■	500-3000 rpm	6	VP,P,FF,O	Profile sander with abrasive wheels.
SPL/8	13		■	500-3000 rpm	8	VP,P,FF,O	Profile sander with abrasive wheels.
LSP/6	13		■	5-40 fps	6	VP,P,FF,O	Profile sander with belts & wheels.
LSP/8	13		■	5-40 fps	8	VP,P,FF,O	Profile sander with belts & wheels.
LBS/4	5		■	5-40 fps	4	VP,P,FF,O	Single-sided edge sander.
LBS/6	5		■	5-40 fps	6	VP,P,FF,O	Single-sided edge sander.
LD/4+4	5		■	5-40 fps	8	VP,P,FF,O	Double-sided edge sander.
LD/6+6	5		■	5-40 fps	12	VP,P,FF,O	Double-sided edge sander.
DCS	13		■	0-1500 rpm	1-10+	FF,LBP,O	Belt and/or wheel profile sanding
BPS	13		■	3-60 fps	1-10+	FF,LBP,O	Belt and/or wheel profile sanding
SEF	5		■	3-60 fps	1-10+	FF,O	Single- or double-sided edge sanding
Delmac Machinery Group, 4322 Piedmont Parkway, Greensboro, NC 27410 Tel: (336) 854-1211 Fax: (336) 854-0811 delmac.com							
Casadei Libra 10 950mm	2		■	4.5-9 m/min	1, 2	Solid wood, veneer	1 combination - rigid platen.
Casadei Libra 30 950mm	2		■	4.5-9 m/min	1, 2, 3	Solid wood, veneer	1 combination or roller combination - rigid or elastic segmented platen.
Casadei Libra 30 1100mm	2		■	4.5-9 m/min	1, 2, 3	Solid wood, veneer	1 combination or roller combination - rigid or elastic segmented platen.
Casadei Libra 40 1100mm	2		■	4.5-9 m/min	1, 2, 3, 4	Solid wood, veneer	1 combination, roller combination, 2 roller, 3 roller, or 2 roller/combination - rigid, elastic or electronic segmented platen.
Casadei Libra 40 1350mm	2		■	4.5-9 m/min	1, 2, 3, 4	Solid wood, veneer	1 combination, roller combination, 2 roller, 3 roller, or 2 roller/combination - rigid, elastic or electronic segmented platen.
Dubois Equipment, P.O. Box 749, Jasper, IN 47546 Tel: (812) 482-3644 Fax: (812) 482-3544							
	10		■		1-2-3	P,FF,VP	Scuff Sanders, Polishers, utilizes varied sanding material.
SN 700	Denibber		■	20-500 fpm	1	VP,P,FF,O	Single head segmented paper style denibbing head for existing conveyors
SBL-12	Denibber		■	20-500 fpm	1	VP,P,FF,O	Single head segmented paper style denibbing head with roller conveyor
SB-12	Profile Scuffer		■	20-500 fpm	7	VP,P,FF,O	Multi-head scuffing sander, sides, top and bottom configurations available
LPS 1207	Profile Scuffer		■	20-500 fpm	7	VP,P,FF,O	Abrasive wheel profile sander
LPS 1210	Profile Scuffer		■	20-500 fpm	10	VP,P,FF,O	Abrasive wheel profile sander
SBD	Scuff Sander		■	5-60 fpm	1,2,3	VP,P,FF,O	Cylindrical heavy-duty scuff sander for white wood, stain or sealer scuffing
RS	Rotary Scuff Sander		■	5-60 fpm	1,2,3	VP,P,FF,O	Rotary scuffing of contoured or 3-D substrates such as kitchen cabinet doors, includes vacuum holddown
DBD	Panel Distressing		■	5-60 fpm	1,2,3	VP,P,FF,O	Wire brush distressing machine for artificially wearing and adding grain texture to cabinet parts and flooring
ES	Scuffing		■	5-60 fpm	1,2,3,4	VP,P,FF,O	Profiled or segmented wheel scuffer for use on edge coating lines
Dynabrade, 8989 Sheridan Drive, Clarence, NY 14031 Tel: (716) 631-0100 Fax: (716) 631-2073							
Dynorbital Supreme	Random Orbital		■			Sanding/finishing	10,000 and 12,000 rpm sanders available in either 3/16" or 3/32" orbits.
Dyninger Sander	Finishing Tool		■	950 rpm		Denib raised grain, defuzz and blend	Air-powered finishing tool.
Lightweight Dyninger	Finishing Tool		■	3,200 rpm		Same as above	Air-powered finishing tool.
Dy-Cut Sanding Stars	Sanding Stars		■			Sanding/finishing	Available in both arbor and spindle mount design.
Dyna-Line Sander	Finishing Tool		■	2,400 strokes/min.			Good for sanding profiles and contours.
Dynorbital Spirit	Orbital Sander		■	12,000 rpm		Sanding/finishing	Lightweight 12,000 rpm sander.
Dynabug II	Finishing Tool		■	10,000 rpm		Finish Sander	Detail sander for corners.
Make your own pad kit	Kit	■					Utilizing urethane mixture, create custom sanding pads to match the profile contour.

APPLICATION: LBP = Lumber & Basic Products VP = Veneer & Plywood P = Particleboard FF = Furniture & Fixtures O = Other
W = Waferboard

TYPE CODE: Numbers in "Type" column are keyed to use descriptions below
 1. Abrasive Planer 3. Drum 5. Edge Sander 7. Open Drum 9. Spool 11. Disc 13. Profile/Custom Sanding
 2. Widebelt 4. Stroke Type 6. Pneumatic Drum 8. Vertical Belt 10. Brush 12. Other 14. Sander for Curved/Irregular Pieces



The resource for woodworking equipment, supplies and services trends

RedBookOnline.com



Brand Name and/or No.	Type	Manual	Auto.	Belt Speed	No. of Heads	Application	Characteristics
Enduro Group, 4390 Airwest Dr. SE, Suite A, Grand Rapids, MI 49512 Tel: (616) 871-9889 Fax: (616) 871-9879							
Duramac 2000	2, 3		■	2,500 sfm	1 or 2	LBP, FF	Entry level & small production shops. Designed especially for cabinet shops.
Duramac 3000	2, 3		■	3,500 sfm	1, 2 or 3	LBP, FF	For medium & large production req. Ideal for furniture, cabinet, fixture & millwork shops.
Duramac 4000	2, 3		■	4,200 sfm	1, 2, 3 or 4	LBP, FF	Heavy duty w/103" belts & robust const. for demanding applications. Avail. w/knife head.
Duramac PS 2000	13		■	Variable	1-8	LBP, FF, O	Profile sanding line w/comb. of head styles for every application. Shaper heads also avail.
European Woodworking Machinery Co., P.O. Box 550, Franklinton, NC 27525 Tel: (919) 494-5197 Fax: (919) 494-7788							
Tagliabue/EuroSander	1,3,10,14		■	16-82	1 to 6	LBP,VP,FF	Heavy-duty, modular construction widebelt sander.
Tagliabue/EuroSander	1,3,10,11		■	16-82	1 to 6	LBP,VP,FF	Heavy-duty, modular construction widebelt sander.
Tagliabue/EuroSander TagL	1,2,3		■	15 to 240 fpm	2 to 4	LBP, P	Top and bottom compact calibrating lines for high production CNC.
Tagliabue Edge Sander ES	5,8,10,14		■	15 to 270 fpm	2 to 20+	LBP,VP,P,FF	Precision, heavy-duty CNC edge sander.
Tagliabue Prof. Sander PS	5,8,10,13, 14		■	15 to 270 fpm	2 to 20+	LBP,VP,FF	Precision, heavy-duty CNC profile sander.
Extrema Machinery Co. Inc., P.O. Box 1450, Albany, LA 70711 Tel: (225) 567-3867 Fax: (225) 567-2966							
Excess A Series	2		■	15-50 fpm	1-3	LBP-FF	Available in 25", 37", 43", 52" wide, 60" belt, heavy-duty mono block construction.
B Series	2		■	15-50 fpm	1-3	LBP-FF	Available 25"-52" wide, 75" belt, heavy-duty mono block construction.
C Series	2		■	15-75 fpm	1-4	LBP-FF	Available 37"-52" wide, 103" belt, heavy-duty construction.
Planer Sander	12		■	15-50 fpm	1-4	LBP-FF, O	Planer-Sander with stealth helical cutterhead widths from 25" - 52"
Felder USA, 1851 Enterprise Blvd., West Sacramento, CA 95691 Tel: (800) 572-0061 Fax: (916) 375-3194							
FS722		4x		82 fpm		LBP,VP,FF	Belt-stroke sander.
Fladder/Hansen & Hundebol, 3402 Oakcliff Road, Ste. B-7, Atlanta, GA 30340 Tel: (770) 452-1271 Fax: (770) 452-7090							
Fladder System	Air-driven					VP, P, FF, O	Fladder for white wood finish sanding & sealer sanding.
Fladder System	Feedthrough					VP, P, FF, O	Stationary feedthrough machine. Fladder for white wood finish & sealer sanding.
Fletcher Machine Co., 4305 E. U.S. Hwy. 64, Lexington, NC 27292 Tel: (800) 438-1054 Fax: (336) 249-6890							
Fletcher-Edge Machine	5, 8, 10, 11	■	■			LBP, FF, O	All types of sanding equipment for trim, shape & sand.
SM-150 Automatic Double Side Edge & Mould Sander	5		■	2800 sfpm	4	P, FF, O	Double-sided edge and mould sander equipped with four belts. Belt dimensions: 220 in. x 4 in.
FM-450 Multiple Brush	10		■	1200 rpm	8	FF	Multiple brush sander with eight Vonnegut brush heads.
Globe Machine Mfg. Co., P.O. Box 2274, Tacoma, WA 98401 Tel: (253) 383-2584 Fax: (253) 572-9672							
	1, 2, 4, 10	■	■		1-6	LBP,VP,FF,O,P	
Globe Sander Model 35D	2		■	Variable	1-6	VP, P, O, W	Continuous duty, widebelt sander, 51" working width. Rough, combination and finish heads avail. May combine 35D sander with specialty saws into a single frame machine.
Globe Brush Finishing Machine Model 35G	10		■	Variable	1 or more	VP, P, O, W	Fine finish or defuzz. and scuffing panel surfaces. Up to 50" wide panels. Brush config. & type per cust. spec. Each brush indiv. driven with indiv. height adj. for prod. thickness.
Grinding and Polishing Machinery Corp., 2801 Tobey Drive, Indianapolis, IN 46219 Tel: (317) 898-0750 Fax: (317) 899-1627							
Brush Backed Sanding Head	10	■				LBP, P, FF	Sands curved & contoured surfaces without pre-forming.
Belt sander	4						
Grizzly Industrial Inc., 1203 Lycoming Mall Circle, Muncy, PA 17756 Tel: (800) 523-4777 Fax: (570) 546-7724							
G9983	Widebelt	■		2050	1	LBP, FF	15"; 5 hp, open-end, w/platen.
G0527	Widebelt		■	3550	1	LBP,VP,FF	18"; 5 hp, vs feed.
G9962Z	Widebelt		■	3500	1	LBP, FF	24"; 10 hp, single-phase, vs feed.
G9962ZX	Widebelt		■	3500	1	LBP, FF	24"; 10 hp, 3-phase, vs feed.
G0582	Widebelt		■	2565	1	LBP, FF	24"; 10 hp, 3-phase, vs feed, w/platen.
G0445	Widebelt		■	2565	1	LBP, FF	24"; 10 hp, 3-phase, vs feed, 75" long belt, w/platen.
G0571	Widebelt		■	2600	1	LBP, FF	37"; 10 hp, single-phase, vs feed, w/platen.
G0539	Widebelt		■	2600	1	LBP, FF	37"; 15 hp, 3-phase, vs feed, w/platen.
G0446	Widebelt		■	2600	1	LBP, FF	37"; 15 hp, 3-phase, vs feed, 75" long belt, w/platen.
G9979	Widebelt		■	2200	1	LBP, FF	43"; 25 hp, 3-phase, vs feed, w/platen.
G9980	Widebelt		■	2200	1	LBP, FF	51"; 30 hp, 3-phase, vs feed, w/platen.
H2933	Widebelt		■	3543, 2565	2	LBP, FF	24"; 15 hp, 3-phase, vs feed, platen on rear head.
H2934	Widebelt		■	3543, 2565	2	LBP, FF	37"; 20 hp, 3-phase, vs feed.
G0447	Widebelt		■	3543, 2565	2	LBP, FF	37"; 20 hp, 3-phase, vs feed, platen on rear head, 75" long belt.
G0581	Widebelt		■	3543, 2565	2	LBP, FF	43"; 25 hp, 3-phase, vs feed, platen on rear head.
G0486	Widebelt		■	3543, 2565	2	LBP, FF	43"; 25 hp, 3-phase, vs feed, platen on rear head, 75" long belt.
G0487	Widebelt		■	3543, 2565	2	LBP, FF	51"; 30 hp, 3-phase, vs feed, platen on rear head, 75" long belt.
G0458	Drum	■		4000	1	LBP, FF	18"; 1.5 hp, 110V, vs feed, open-end.
G0459	Drum		■	2300	1	LBP, FF	12"; 1.5 hp, 110V, vs feed, benchtop design.
G1079R	Drum	■		2100	2	LBP, FF	16"; 2 hp, 220V, non-rubberized drums, heavy-duty conveyor.
G1066R	Drum	■		2300	2	LBP, FF	24"; 5 hp, 220V, non-rubberized drums, heavy-duty conveyor.
APPLICATION: LBP = Lumber & Basic Products VP = Veneer & Plywood P = Particleboard FF = Furniture & Fixtures O = Other W = Waferboard							
TYPE CODE: Numbers in "Type" column are keyed to use descriptions below							
1. Abrasive Planer 3. Drum 5. Edge Sander 7. Open Drum 9. Spool 11. Disc 13. Profile/Custom Sanding							
2. Widebelt 4. Stroke Type 6. Pneumatic Drum 8. Vertical Belt 10. Brush 12. Other 14. Sander for Curved/Irregular Pieces							

SANDING & FINISHING

Brand Name and/or No.	Type	Manual	Auto.	Belt Speed	No. of Heads	Application	Characteristics
Grizzly Industrial Inc., 1203 Lycoming Mall Circle, Muncy, PA 17756 Tel: (800) 523-4777 Fax: (570) 546-7724 Continued							
G1066Z	Drum	■		2300	2	LBP, FF	24"; 5 hp, 220V, vs feed, hook/loop drums, heavy-duty conveyor.
G0449	Drum	■		2800	2	LBP, FF	36"; 10 hp, single-phase, vs feed, non-rubberized drums.
G0450	Drum	■		2800	2	LBP, FF	36"; 15 hp, 3-phase, vs feed, non-rubberized drums.
G1531	Edge Sander			1800		LBP, FF	6" x 80" belt, 1.5 hp, 110/220V, adjustable table, benchtop design.
G1140	Edge Sander			1800		LBP, FF	6" x 80" belt, 1.5 hp, 110/220V, adjustable table.
G0512	Edge Sander			1800		LBP, FF	6" x 80" belt, 1.5 hp, 110/220V, large wraparound table.
G0563	Edge Sander			3150		LBP, FF	6" x 89" belt, 2 hp, 220V, oscillating belt, drum attachment.
G0564	Edge Sander			3150		LBP, FF	6" x 108" belt, 3 hp, 220V, oscillating belt, drum attachment.
G9984	Edge Sander			4120		LBP, FF	9" x 138.5" belt, 3 hp, 220V, single-phase, oscillating belt.
G9985	Edge Sander			4120		LBP, FF	9" x 138.5" belt, 3 hp, 220V, 3-phase, oscillating belt.
G5394	Stroke Sander			3500		LBP, FF	6" x 186" belt, 3 hp, 220V, large table & movable platen.
G1071	Osc. Spindle			1725		FF	25" x 25" table, 10 spindle sizes included.

Holz-Her US Inc., 5120 Westinghouse Blvd., Charlotte, NC 28273 Tel: (704) 587-3400 Fax: (704) 587-3419							
Kundig Topiq	2		■	9-45 fpm	1, 2, 3	LBP, VP, P, FF	Solids, veneers.
Kundig Magiq	2		■	9-45 fpm	1, 2	LBP, VP, FF, O	Solids, veneers, sealers/lacquers.
Kundig Primo	2		■	9-45 fpm	1	LBP, VP, P, FF, O	Solids, veneers, sealers/lacquers.
Kundig Duplex	2		■	9-45 fpm	2	LBP, VP, P, FF, O	Solids, veneers, sealers/lacquers.
Kundig Triplex	2		■	9-45 fpm	3	LBP, VP, P, FF, O	Solids, veneers, sealers/lacquers.
Kundig Quadrex	2		■	9-45 fpm	4	LBP, VP, P, FF, O	Solids, veneers, sealers/lacquers.
Kundig Pinnacle	1,2		■	9-250 fpm	1-6	LBP, VP, P, FF, O	24/7 operation w/Kundig equipment. 53" - 86" widths.
Kundig CNC	2		■	2-75 fpm	1	LBP	Lineal Profile Contour sanding. 25"-63" widths.
Kundig Uniq	5	■			1	LBP, VP, FF	2 fixed work sides for veneer or hardwood; spindle sanding
Kundig Uniq S	5	■		9-45 fpm	1	LBP, VP, FFO	Conveyor fed edge sanding for veneer, hardwood, sealers
Kundig HPL	2		■	0-250	1	VP	For sanding high pressure laminate/raw veneer sheets and rolls. Thickness range: 0.010" to 2.0".
Kundig Premium	1,2		■	9-45 fpm	1 to 6	LBP, VP, FF, O	Fixed conveyor height, smart set, touchscreen, contact rolls, air pad (std), electronic pad, cross belt, cutterhead. 25" to 75" widths.
Kundig Brilliant	2		■	9-45 fpm	1 to 6	LBP, VP, FF, O	Brilliant unit(s), plus standard kundig equipment. 43" to 75" widths.
Boarke K	2		■	7-45 fpm	1	LBP	Heavy-duty widebelt sanders; 25", 37", 43", 52", 62" widths
Boarke RK	2		■	7-45 fpm	2	LBP, O	Heavy-duty widebelt sanders; 25", 37", 43", 52", 62" widths
Boarke RRK	2		■	7-45 fpm	3	LBP, O	Heavy-duty widebelt sanders; 25", 37", 43", 52", 62" widths
Boarke NK or NR	2		■	7-45 fpm	2	LBP	Heavy-duty planer sanders; 25", 37", 43", 52", 62" widths
Boarke NRK	2		■	7-45 fpm	3	LBP	Heavy-duty planer sanders; 25", 37", 43", 52", 62" widths
Boarke Brush Sanders	10		■	7-45 fpm	2-5	LBP, VP, FF, O	Variable speed controls, reversible brushes

Lobo Machinery Corp., 13731 Proctor Ave., City of Industry, CA 91746 Tel: (626) 369-6500 Fax: (626) 369-6677							
FL-901	6, 10	■		2599 fpm	1	All	Pneumatic drum sander.
EGS-132	5, 13	■		3500 fpm	1	All	Edge sander.
EGS-947	5, 14	■		3500 fpm	1	All	Oscillating edge sander.
RC-420V	3, 6, 8, 10, 13, 14		■	Variable	1	All	Round pole curve sander.
SD-VC506A	3, 6, 8, 10, 13, 15		■	Variable	2	All	Curve sander two side.
SD-905MU	3,5,6,9,10,11,13		■	Variable	Any	All	Moulding, 4-side sander.
CS-2C2S	8, 10, 11, 12, 13		■	3500 fpm	Any	All	Shape and sand.
PS-2K82CB	8, 10, 11, 12, 14		■	3500 fpm	Any	All	Shape and sand.
CA-1554	3, 6, 8, 10, 12, 13		■	Variable	1	All	Flat, curve, texturing sander.
WS-DA3760, DDA5275	2		■	Variable	1 to 4	All	Any size, widebelt heads, combination.
WS-52SSW	2		■	Variable	1 to 4	All	Top and bottom, any size, widebelt heads, combination.
WS-NDAA900	1, 2		■	Variable	1 to 4	All	Planer head, any size, widebelt heads, combination.
WS-1000 HB	2, 10, 12		■	Variable	1 to 4	All	Special orbital profile sanding, any size, widebelt heads combination.
WSB-3760	2		■	Variable	1 to 2	All	Special stain, coating sanding, any size, widebelt heads combination.

Macoser Inc., P.O. Box 667789, Charlotte, NC 28266 Tel: (704) 392-0110 Fax: (704) 394-0410							
Torreda	12		■		1-2	FF, O	Turning.

Makor U.S.A. Inc., 1455 Oakbrook Parkway, Norcross, GA 30093 Tel: (770) 368-0047 Fax: (770) 368-0059							
LF 4 / LF 6	13		■	Feed belt 40-200 fpm	4-8	VP, P, FF, LBP, O	Profile sander with fladder wheels.
LX 4	13		■	Sanding belt 21 fpm Feed belt 40-330 fpm	4 or 6	VP, P, FF, LBP, O	Profile sander with 4 or 6 wheels.
LC 6	13		■	Same	1-15	VP, P, FF, LBP, O	Profile sander with belts and wheels. Up to 8" width profiles.
LP 8	13		■	Same	1-21	VP, P, FF, LBP, O	Profile sander with belts and wheels. Up to 12" width profiles.
PEGASO 10	13		■	Same	8	VP, P, FF, LBP, O	Panel sander with wheels.

Midwest Group One, 2645 26th Ave., Minneapolis, MN 55406 Tel: (612) 721-5347 Fax: (612) 721-1736							
Patriot 1	2		■	3400	1	LBP, VP, P, FF	
Patriot 2	2		■	3600	2, 3	LBP, VP, P, FF	
Explorer	1 & 2		■	1800-3600	1, 2, 3, 4	LBP, VP, P, FF, D	
Titan	1 & 2		■	2200	1	LBP, VP, P, FF	
Tomahawk	1, 2, 12		■	Variable	3, 4	LBP	

Mill Spec Machine/Loewer, 508 Creske Ave., Rothschild, WI 54474 Tel: (715) 355-0712 Fax: (715) 355-0775							
DiscMaster	10, 11, 13, 14		■	5-50 fpm	2 brushes; 16 discs	LBP, VP, P, FF, O	A combination of eccentric discs and sanding strip brushes for white wood and sealer sanding profiled products.
RotoMaster	10, 13, 14		■	5-50 fpm	2-4 brushes	LBP, VP, P	Sanding strip brushes for white wood sanding and sealer sanding panels.
EcoSand	10, 13, 14		■	6-30 fpm	2 brushes	LBP, VP, P	Economic and compact unit for white wood and sealer sanding flat and profiled products.
MultiMaster	10, 11, 12, 13		■	up to 150 fpm	unlimited	LBP, VP, P, FF, O	Multihead disc, brush and belt brush technology for white wood and sealer sanding mouldings and lineal products.
EcoCat	12, 13		■	up to 150 fpm	belt brush	LBP, VP, P, O	Belt brush technology that can be mounted behind any moulder, profiler, wrapper of finishing system

APPLICATION: LBP = Lumber & Basic Products VP = Veneer & Plywood P = Particleboard FF = Furniture & Fixtures O = Other
W = Waferboard

TYPE CODE: Numbers in "Type" column are keyed to use descriptions below

1. Abrasive Planer	3. Drum	5. Edge Sander	7. Open Drum	9. Spool	11. Disc	13. Profile/Custom Sanding
2. Widebelt	4. Stroke Type	6. Pneumatic Drum	8. Vertical Belt	10. Brush	12. Other	14. Sander for Curved/Irregular Pieces

Brand Name and/or No.	Type	Manual	Auto.	Belt Speed	No. of Heads	Application	Characteristics
Nash Co/Crouch Machiner., 6516 Seven Lakes Village, West End, NC 27376 Tel: (910) 673-0611 or (800) 344-1948 Fax: (910) 673-0615							
NASH 345	10-12		■	N/A	10 Spin.	O	A 10 spindle turning sander available in 32, 56, 72 & 96" lengths. Five row sanding rack. Production rate: 10-30 pieces. per minute.
NASH 270	10, 12		■	N/A	4 spindle and 6 spindle	Other	4- or 6-spindle turning sander avail. in 40", 48" or 56" lengths. Spindle speed 250-1800 rpm. Production rate: 4-16 pieces/min. 5-hp drive motor, 1/2-hp feed motor. 3/4" oscillation. Dust curtain.
NASH 330	10, 12		■	250-1800 rpm	Single spindle	O, LBP, FF	Single spindle auto. turning sander, 3/4"-3" dia. & 3"-56" length turnings. 4 row rack.
Opti-Sand Inc., 1120 N. Ridge Ave., Lombard, IL 60148 Tel: (877) 533-6784 or (630) 953-1245 Fax: (877) 533-7263 or (630) 953-1214							
L Series	5,6,10,11,12,13,14	■	■	10-400 fpm	1-12	LBP, VP, FF, O	Moulding sander using flexible finger and other abrasives for white wood and sealer sanding, 1-4 sides of mouldings and other linear parts.
R Series	10,12,13,14		■	4-44 fpm	4	LBP, VP, FF, O	Rotary brush sander for white wood and sealer sanding of doors, drawer fronts, trim and more.
P Series	10,12,13,14		■	4-44 fpm	1-6	LBP, VP, FF, O	1 to 6 spindles fixed across the conveyor for white wood and sealer sanding of mouldings, doors, flat panels and more.
UTS	5,6,10,13,14	■		N/A	1	LBP, FF, O	Table sander with tilting, spindle and variable spindle speed
ES224	5,6,10,13,14	■		N/A	2	LBP, FF, O	Twin spindle pedestal type sander with variable spindle speed and power adjustable spindle height
Powermatic Corp., WMH Tool Group, 2420 Vantage Drive, Elgin, IL 61024 Tel: (847) 851-1000 Fax: (847) 851-1045							
OES9138	5	■		3542 sfm	1	LBP, FF, VP, W	9 x 139 oscillating edge sander, tilting table, 18" radius end worktable.
31A	8-11			2410 sfpm		LBP, FF, VP, W	6 x 48 belt, 12" disc sander.
WB43	2		■		1 comb.		43x75 belt, 25 hp drive motor.
WB25	2		■		1 comb.		25x75 belt, 15 hp drive motor.
WB37	2		■		1 comb.		37x75 belt, 20 hp drive motor.
1632	2			2200 sfpm	1 comb.	LBP, FF	Medium production general wood products.
Model 6108	5	■		3150 sfpm		LBP, VP, P, FF	Table for drum sanding, 4" dust collection, shroud, belt tilts to 90°.
DS 20	11	■				LBP, VP, FF, W	20" sanding disc.
RAMCO, 0-794 Chicago Drive, Jenison, MI 49428 Tel: (616) 457-5999 Fax: (616) 457-3620							
SL2514/24	1,3		■	Variable	1,2	LBP, VP, P, O	25" wide single or double drum sander w/ single- or three-phase motor.
SL3714/24	1,3		■	Variable	1,2	LBP, VP, P, O	37" wide single or double drum sander w/ single- or three-phase motor.
PACESETTER Series	2		■	20-80 fpm	1 or 2	VP, P, FF, O	Medium production 4 jack elevating system.
PACESETTER DW-900KP	12		■		2	LBP, P, FF, W	Economical medium duty knife planer/sander combination.
Series 60	2		■	20-80 fpm	1 or 2	VP, P, FF, O	Medium duty—light production 12" and 37" widths.
Series 75, Series 84	2		■	20-80 fpm	1, 2 or 3	VP, P, FF, O	Continuous—medium production.
Series 103	2		■	30-90 fpm	1, 2 or 3	VP, P, FF, O	Continuous duty—heavy production 32" to 62" widths.
Series 1000	1		■	15-45 fpm	Single top & bottom	LBP, P, O	Abrasive planing applications up to 30 hp, 25" to 31" widths.
Series 2000	1		■	20-60 fpm	See above	LBP, P, O	Abrasive planing applications up to 50 hp, 25" to 37" widths.
Series 4000	1		■	25-75 fpm	See above	LBP, P, O	Abrasive planing applications up to 100 hp, 25" to 31" widths.
Series 8000	1		■	25-100 fpm	See above	LBP, P, O	Abrasive planing applications up to 150 hp, 32" to 50" widths.
Abrasive Brush	10		■	Variable	See above	VP, P, FF, O	Fine finish, or defuzz, white wood panels & scuff sanding sealed panels. 18" -62" widths.
Ritter Mfg. Inc., 1300-B W. 4th St., Antioch, CA 94509 Tel: (510) 757-7296 Fax: (925) 757-7083							
Ritter R-700 & R-900	5	■		2700 fpm	1	LBP, VP, P, FF, O	2 work tables, 2 platens, tilting table, dust collector.
CR1813	6, 14	■			2	FF, O	Std. machine 3-hp motor, magnetic electrics, spindle size 1 1/4" x 9"
CR3553	13	■		0-1,800 rpm	1	LBP, VP, FF, P, O, W	Single spindle, abrasive wheel, variable speed tilting profile sander.
CR353E	13		■	0-1,800 rpm	3	LBP, VP, FF, P, O, W	Automatic shaper/sander, variable speed, digital control, 0-20 fpm.
CR245	5	■		3,700-fpm		LBP, VP, FF, P, O, W	Osc. or non-osc. edge belt sander available in 40", 48", 50" or 64" lengths. Numerous options. 6", 8" or 10" belt widths.
CR205	5	■		3,100-fpm		LBP, VP, FF, P, O, W	Osc. or non-osc. edge belt sander available in 4", 5" or 6" belt widths. 50" platen. Numerous options.
R911	5, 14	■		2,700 fpm	1	LBP, FF	Non oscillating.
CR258	5, 14	■		2,700 fpm	1	LBP, FF	Oscillating.
CR354	10, 13	■		0-1800 rpm	1	LBP, FF	Non tilting spindle.
CR366E	13		■	0-1800 rpm	4	LBP, VP, P, FF	Arch cutting tilting spindles.
CR367E	13		■	0-1800 rpm	4	LBP, VP, P, FF	Jump cope, tilting spindles.
SCM Group North America, 2475 Satellite Blvd., Duluth, GA 30096 Tel: (770) 813-8818 Fax: (770) 813-8819							
Sandya 1/S CS 95 Plus	2		■	15/30 fpm	1	LBP, VP, FF, O	18 hp, 37" x 60" belt size for small to medium shops.
Sandya 3/S	2		■	15/30 fpm	1 or 2	LBP, VP, P, FF, O	18-24 hp, 37" x 75" or 43" x 75" belt size, for small to medium shops.
Sandya 5/S	1, 2		■	Variable	1, 2 or 3	LBP, VP, P, FF, O	18-34 hp, 43" x 85" or 53" x 85" belt size for medium shops.
Sandya 16/S	1, 2		■	Variable	2 or 3	LBP, VP, P, FF, O	18-36 hp, 43" x 103" or 53" x 103" belt size for medium shops.
DMC Eurosand L	2		■	15-60 fpm	2, 3 or 4	LBP, VP, P, FF, O	18-48 hp, 43" or 53" belt size for medium to large shops with high production rates.
DMC Unisand K	1, 2		■	15-60 fpm	2, 3, 4, 5 or 6	LBP, VP, P, FF, O	18-60 hp, 43", 53" and 65" for large shops.
DMC Topsand K	2		■	Variable	1, 2, 3 or 4	LBP, VP, P, FF, O	30-100 hp, 53" and 65" belt size for large, high production shops.
DMC Masterbrush	10, 13		■	15-60 fpm	2, 3, 4 or 5	LBP, VP, P, FF, O	18-30 hp brush sander, 53" capacity.
DMC Mastersand	1, 2		■	15-60 fpm	2, 3 or 4	LBP, VP, P, FF, O	18-48 hp, 43" or 53" belt size for medium to large shops.
DMC Linee Unisand K	2		■	Variable	1, 2, 3 or 4	LBP, VP, P, FF, O	18-48 hp, 43", 53" or 65" belt size for large shops with limited space.
DMC Parquet Lines	1, 2		■	Variable	1, 2, 3 or 4	LBP, VP, P, FF, O	18-75 hp, 43" or 53" belt size for multiple shift usage, top and bottom sanding, flooring.
DMC Eurometal	2, 12		■		1, 2 or 3	O	18-48 hp, 43" or 53" for metal sanding and deburring.
Safety Speed Cut Mfg., 13943 Lincoln St. N.E., Ham Lake, MN 55304 Tel: (763) 755-1600 Fax: (763) 755-6080							
3760	2		■	0 - 18 fpm	1	LBP, VP, P, FF, O, W	Utilizes a 37" x 60" sanding belt, has dust-free photo electric eye tracking system, variable speed conveyor belt & a 2-1/2" removable platen. Avail. w/10 hp single or 15 hp 3-ph motor.
4375	2		■	0 - 18 fpm	1	LBP, VP, P, FF, O, W	Utilizes a 43" x 75" sanding belt. For heavier production, w/fully adjustable platen, variable speed DC powered conveyor table and 7-3/4" throat. Avail. w/10 hp single or 20/30 hp 3-ph motor.
Sioux Tools Inc., 250 Snap On Drive, Murphy, NC 28906 Tel: (800) 722-7290 or (828) 835-9765 Fax: (800) 722-7236							
Disc Sanders	11, 12	■					Others include orbital disc and vacuum pick-up.

APPLICATION: LBP = Lumber & Basic Products VP = Veneer & Plywood P = Particleboard FF = Furniture & Fixtures O = Other
W = Waferboard

TYPE CODE: Numbers in "Type" column are keyed to use descriptions below
 1. Abrasive Planer 3. Drum 5. Edge Sander 7. Open Drum 9. Spool 11. Disc 13. Profile/Custom Sanding
 2. Widebelt 4. Stroke Type 6. Pneumatic Drum 8. Vertical Belt 10. Brush 12. Other 14. Sander for Curved/Irregular Pieces

SANDING & FINISHING

Brand Name and/or No.	Type	Manual	Auto.	Belt Speed	No. of Heads	Application	Characteristics
-----------------------	------	--------	-------	------------	--------------	-------------	-----------------

Silver Machine Inc., 160 W. Beaver Creek Road, Unit 3, Richmond Hill, ON L4B 1B4 Canada Tel: (888) 354-3388 Fax: (905) 881-8193

Silver SPR-600DA	2		■		2	LBP,VP,P,FF,W	Auto elevation of conveyor table by digital readout, sanding belt quick change device.
Silver SPR-900DA	2		■		2	LBP,VP,P,FF,W	Auto elevation of conveyor table by digital readout, sanding belt quick change device.
Silver SPR-1100DA	2		■		2	LBP,VP,P,FF,W	Auto elevation of conveyor table by digital readout, sanding belt quick change device.
Silver SPR-1300DA	2		■		2	LBP,VP,P,FF,W	Auto elevation of conveyor table by digital readout, sanding belt quick change device.
Silver SHD-1300DDA	2		■	4-18 mpm	3	LBP,VP,P,FF,W	Auto elevation of conveyor table by digital readout, sanding belt quick change device.

SlipCon USA Inc., 1301 Larc Industrial Blvd., Burnsville, MN 55337 Tel: (877) 754-7266 or (952) 746-2330 slipcon.com

Perfection VS DD	10,11,13		■	0-30 fpm	9	LBP,VP,FF,O	Vertical brush sander to integrate into a hang-line finish line. With vacuum bed, adjustable disc rpm, disc oscillation, sanding depth & feed speed.
Perfection U-BBDD	10,11,13		■	0-30 fpm	11	LBP,VP,FF,O	40", 52", 64" or 72" top & bottom brush sander for sanding doors, face frames, drawer fronts & panels. For whitewood & sealer sanding w/ patented comb. of rotating & oscillating discs & rollers.
Perfection 2U-BBDD	10,11,13		■	0-50 fpm	15	LBP,VP,FF,O	40", 52", 64" or 72" top & bottom brush sander for sanding doors, face frames & panels. For whitewood, stain & sealer sanding with rotating, oscillating discs & rollers. PLC controls, vacuum bed & panel cleaner.
Perfection BBDD	10,11,13		■	0-50 fpm	13	LBP,VP,FF,O	40", 52", 64" or 72" top brush sander for sanding doors, face frames & panels. For whitewood, stain & sealer sanding w/ rotating, oscillating discs & rollers. PLC controls, vacuum bed and panel cleaner.
Perfection DD	10,11,13		■	0-50 fpm	11	LBP,VP,FF,O	40", 52", 64" or 72" top brush sander for sanding doors, drawer fronts & face frames. For whitewood, stain & sealer sanding w/ rotating, oscillating discs. PLC, vacuum bed & panel cleaner.
Excel	10,13		■	0-50 fpm	2,3,4	LBP,VP,FF,O	52" top brush sander w/ 2, 3, or 4 brushes for straightline sanding of doors, panels and flooring. For whitewood, stain & sealer sanding, w/ PLC, vacuum bed & panel cleaner.

Stiles Machinery Inc., 3965 44th St. S.E., Grand Rapids, MI 49512 Tel: (616) 698-7500 Fax: (616) 698-9411 stilesmachinery.com

Bütfering SCO	2		■	2.5-13 mpm 4 to 20 mpm 5 to 25 mpm	1-4	LBP,VP	43" or 53" widths, constant pass-line, available with contact roller, planer head, air pad, combustion head, CPS segmented pad, cross belt, longitudinal belt, 85" or 103" abrasive belts.
Bütfering SBR	2, 10		■	2.5-13 mpm	1-4	VP	53" width, constant pass-line, either drum brushes, oscillating disc brushes or segmented pad heads available for breaking edges and sanding profiles.
Bütfering SCR	2		■	2.5-13 mpm 4 to 20 mpm 5 to 25 mpm	1-4	LBP,VP	53" or 65" widths, constant pass-line, available with contact roller, planer head, air pad, combination head, CPS segmented pad, cross belt, longitudinal belt, 103" abrasive belts. Top and bottom machines available.
Heesemann Impression	2		■	3-15 mpm	1-4	LBP,VP,P,FF,O	43" & 52" widths, constant pass line, CSD segmented pad, avail. w/contact roller, crossbelt, longitudinal belt, 85" or 103" abrasive belts. Also avail. w/enhanced finish heads.
Heesemann MFA 10	1, 2		■	5-15 mpm	1-4	LBP,VP,P,FF,O	52" widths, constant pass line, CSD segmented pad, avail. w/ planer head, contact roller, cross belt, and longitudinal belt, 85" or 103" abrasive belts. Also avail. w/enhanced finish heads. Can also be produced in a bottom configuration with 103" abrasive belts.
Heesemann LSM 8-S	1, 2		■	3-15 mpm	1-4	LBP,VP,P,FF,O	52" widths, constant pass line, CSD segmented pad, avail. w/ planer head, contact roller, crossbelt, longitudinal belt. Can also be produced in bottom configuration, 103" abrasive belts.
Heesemann LSM 8	2		■	5-25 mpm, 6-30 mpm 8-40 mpm 12-60 mpm	1-8	LBP,VP,P,FF,O	52" widths, constant pass line, CSD segmented pad, avail. w/ contact roller, cross belt & long. belt. Can also be produced in bottom configuration, 103" & 128" belts. Also avail. w/finished heads & orbital OSR heads.
Heesemann KSA 8	2		■	5-25 mpm, 6-30 mpm 8-40 mpm 12-60 mpm	1-8	LBP,VP,P,FF,O	52", 62", 70", 78" & 86" widths, constant pass line, CSD segmented pad, avail. w/contact roller, cross belt, longitudinal belt. Can be made in bottom config., 103" & 128" belts. Also avail. w/enhanced finish heads.
Heesemann UKP	13, 14		■	5-25, 6-30 mpm	As required	LBP,VP	Profile cutting & sander, single or double sided, single profiles or turret applications, CNC.
Heesemann FBA	2		■	5-25	1-4	VP	12" to 52" widths, constant pass-line, electronically positioned contact rollers able to sand to a 0.012" thickness, 103" abrasive belts.
Heesemann SZ-2	14		■	CNC	1-4	LBP,VP	CNC edge sander for odd-shaped parts.
Heesemann BM-8	2, 10		■	3-15 mpm	1-6	VP,F,O	52" width, constant passline, avail. w/drum brushes, unique RUT planetary disc, CSD segment pads for surface sanding & breaking the edge of 3-D parts, recessed panel doors or curved & profiled parts.

Stiles Shop Solutions, 3965 44th St. S.E., Grand Rapids, MI 49512 Tel: (616) 698-8456 Fax: (616) 698-9411

SBO 109	2		■	Fixed	1	LBP,P,FF,O	Combi head.
Butturing 100 series	1,2		■	8-42 fpm	1,2,3	LBP,VP,P,FF,O	43" wide, widebelt, segmented pad, air cushion pad, planer head, 75" belts
Butturing 300 series	2		■	8-42 fpm	1,2,3	LBP,VP,P,FF,O	53" wide, constant passline, widebelt, cross belt, EPS segmented pad, 103" belts
SGO series	2		■	Multiple	1 to 4	LBP,VP,P,FF,O	Combi, air cushion pad.
SKO series	2		■	Variable	1 & 2	LBP,VP,P,FF,O	Roller, combi, segmented pad.
SCO series	2		■	Variable	1 to 4	LBP,VP,P,FF,O	Planer sanders - veneer and sealer sanding

SuperMax Tools, 1275 Corporate Center Drive, Eagan, MN 55121 Tel: (651) 454-3401 Fax: (651) 454-3465 supermaxtools.com

SHOPPRO 25	25" drum sander type 1,3		■	0-10 fpm (inf. var.)	1	LBP,VP,FF,O	Precise, uniform thickness dimensioning, veneer sanding without a press-back application. Edge sanding and light dimensioning of wide stock. Excellent finish sanding. Abrasives available from 36-220 grit in pre-cut strips and pre-marked bulk rolls. Stock as short as 2-1/4"; as wide as 25".
SUPERMAX 25	25" drum sander; type 1, 3		■	0-15 fpm (SmartSand cont.) -	1	LBP,VP,FF,O	Abrasive plane, dimension or finish sand. Dimension stock to within .010" uniform thickness. SandSmart automatically adjusts conveyor rate giving a smooth & flat finish. Abrasives available from 36-220 grit in pre-cut strips and pre-marked bulk rolls. Stock as short as 2-1/4"; as wide as 25".
SUPERMAX 25 x 2	25" drum sander type 1, 3		■	0-15 fpm (SmartSand cont.)	2	LBP,VP,FF,O	Same as above. Stock as short as 3-1/2"; as wide as 25".
SUPERMAX 37	37" drum sander type 1, 3		■	0-15 fpm (SmartSand cont.)	1	LBP,VP,FF,O	Same as above. Stock as short as 2-1/4"; as wide as 37".
SUPERMAX 37 x 2	37" drum sander type 1, 3		■	0-15 fpm (SmartSand cont.)	2	LBP,VP,FF,O	Same as above. Stock as short as 3-1/2"; as wide as 37".
SUPERMAX 50 x 2	50" drum sander type 1, 3		■	0-15 fpm (SmartSand cont.)	2	LBP,VP,FF,O	Same as above. Stock as short as 3-1/2"; as wide as 50".
SUPERBRUSH 24	24" brush sander; type 10, 13, 14		■	0-15 fpm (inf. var.) Brush speed 400- 1200 RPM	1	LBP,VP,P,FF,O,W	Distress wood and composites, sealer sanding, polishing, contour & irregular surface sanding, cleaning and deburring. Available brushes include wire, nylon, nylon w/ abrasives, abrasive and natural fiber. All brushes avail. in a variety of configurations, styles & grits. Stock as short as 10"; as wide as 24".
SUPERBRUSH 36	36" brush sander type 10, 13, 14		■	Same as above	1	LBP,VP,P,FF,O,W	Same as above. Stock as short as 10"; as wide as 36".
SUPERBRUSH 49	49" brush sander type 10, 13, 14		■	Same as above	1	LBP,VP,P,FF,O,W	Same as above. Stock as short as 10"; as wide as 49".

APPLICATION: LBP = Lumber & Basic Products VP = Veneer & Plywood P = Particleboard FF = Furniture & Fixtures O = Other
W = Waferboard

TYPE CODE: Numbers in "Type" column are keyed to use descriptions below

1. Abrasive Planer	3. Drum	5. Edge Sander	7. Open Drum	9. Spool	11. Disc	13. Profile/Custom Sanding
2. Widebelt	4. Stroke Type	6. Pneumatic Drum	8. Vertical Belt	10. Brush	12. Other	14. Sander for Curved/Irregular Pieces

Brand Name and/or No.	Type	Manual	Auto.	Belt Speed	No. of Heads	Application	Characteristics
SuperMax Tools, 1275 Corporate Center Drive, Eagan, MN 55121 Tel: (651) 454-3401 supermaxtools.com Continued							
SUPERBRUSH 13	13" brush & drum 1, 3, 10, 13, 14		■	Same as above	1	LBP, VP, P, FF, O, W	Same as above. Stock as short as 9", as wide as 13".
SUPERBRUSH 36x2	36" brush & drum 10, 13, 14		■	0-30 fpm		LBP, VP, P, FF, O, W	Same as above. Stock as wide as 36".
SUPERBRUSH 52x2	52" brush & drum 10, 13, 14		■	12-60 fpm		LBP, VP, P, FF, O, W	Same as above. Stock as wide as 52".
SUPERMAX WB Series	25", 37", 43", 51" 2		■	16-62 fpm		LBP, VP, P, FF, O	Heavy-duty industrial widebelt sanders.
SUPERMAX WB x 2 HD Series	25", 37", 43", 52" 2		■	16-62 fpm		LBP, VP, P, FF, O	Heavy-duty industrial widebelt sanders.
SUPERMAX WB x 3 HD Series	25", 37", 43", 52" 2		■	16-62 fpm		LBP, VP, P, FF, O	Heavy-duty industrial widebelt sanders.
SUPERMAX WBP x 3 HD Series	37", 43", 52" widebelt/planer		■	16-62 fpm		LBP, VP, P, FF, O	Heavy-duty industrial widebelt/planer combination.
Tech Mark Inc., 7901 Industry Ave., North Little Rock, AR 72117 Tel: (501) 945-9393 Fax: (501) 945-0312							
PAO MACC LRN/4	13		■	50-260 fpm	4 to 10	VP, P, FF, O	Profile sander w/belt and wheels. Automatic compensation heads.
Timesavers Inc., 11123 89th Ave. N., Maple Grove, MN 55369 Tel: (800) 537-3611 or (763) 488-6600 Fax: (763) 488-6601							
Series 1300	2		■		1-2	LBP, FF, O	Industrial level widebelts, planer/sanders and orbitals.
Series 2300	2, 12		■		1-3	LBP, FF, VP, O	Planer/sanders, veneer sanders, widebelts.
Series 3300	1, 2, 12		■		1-4	LBP, FF, VP, O	Heavy-duty widebelts, planer/sanders and orbitals.
Series S300	1, 2, 12		■		1-8	LBP, FF, VP, O	Heavy-duty production sanders.
Series 400-P	2, 12		■		1-6	VP, P, W, O	Heavy-duty production sanders.
Speedsander	2		■		1-2	LBP, FF, O	25, 37, & 43" portable widebelt sanders for smaller shop environments
Turbosand, P.O. Box 516, Anderson, CA 96007 Tel: (877) 348-8726 Fax: (530) 365-1007							
Turbosand Preformed Rotary & Sanding Sys.	5, 11, 13, 14		■	80-220 grits	As required	LBP, VP, FF, O	3", 5", 6", & 8" heads mount on single or multi-station machine w/ 3/4" to 1-1/4" spindles. Abrasive strips die-formed to match common edges & intricate profiles lock into head.
TurboFlex Rotary Brush/Sanding	5, 10		■	Various grits		LBP, VP, FF, O	Various diameters for sanding flat panels, mouldings, backcuts on raised panels & outside edges. Abrasive refills & brushes easily installed/replaced.
TurboFlex Pro Profiled Brush Sanding	5, 13		■	120-220 grit		LBP, VP, FF, O	Profiled abrasive flap sander to match profile. Abrasive refills & brushes easily installed & replaced.
US Concepts Inc., 1120 Ridge Ave., Lombard, IL 60148 Tel: (630) 268-9117 Fax: (630) 268-9197							
FAS	14		■	1600 rpm	1	Curved mouldings	Arch moulder-sander for curved mouldings. (Radii, circles, ellipses, etc.)
HN Series	13		■	57 fps or variable	2-6	VP, P, FF, LBP, O	Profile sander with combination of wheels and belts.
Unique Machine & Tool Co., 4232 East Magnolia St., Phoenix, AZ 85034 Tel: (602) 470-1911 Fax: (602) 470-1916							
Model 275 Profile sander	12, 13, 14	■		Variable	1	LBP, FF	Abrasive wheels—various shapes, tilts with variable speed.
Model 4512 shaper/sander	5, 13, 14		■	Variable	3	LBP, VP, P, O	Variable speed shaping and sanding system. Reversible variable speed sanding stations, variable speed conveyor, digital positioning on infeed and sanding heads, 45 degree tilt on sander.
Model 4522	5, 13, 14		■	Variable	4 stacked	L, VP, P, O	4-station shape and sand with stack tooling capacity, feed rate to 35 lfm, climb cutting feature, variable speed on conveyor and sanding.
Model 375	5, 8, 10, 12		■	Variable	1 - 8	mouldings	Designed for production sanding of moulding, denibbing, sealer and finishing sanding.
Voorwood, 2350 Barney St., Anderson, CA 96007 Tel: (530) 365-3311 Fax: (530) 365-3315							
A-111 Profile Shaper Sander	5, 13		■	N/A	3	LBP, VP, MDF, FF	Shaper followed by two counter rotating sanding heads, shapes and sands edges in one pass. All stations adjust up and down and tilt 45° to save set-up time.
A-112 Profile Shaper	5, 13		■	N/A	4	LBP, VP, P, MDF, FF, O	Two shapers followed by two counter rotating sanders; shapes and sands complicated profiles and raised panels in one pass; all stations adjust up and down and tilt S/B 0-45°. Excellent for volume production of hardwood raised panels.
A-125 Profile Shaper	5, 13		■	Variable	3, 4		
A-178 Profile Shaper Sander	5, 13		■	N/A	6	LBP, VP, P, MDF, FF, O	High speed (35fpm), shaper sander with 2 shaping heads & 4 sanding heads. Shapes & finish sands in one pass. Excellent for complicated profiles and raised panels.
A115	5, 13		■	Variable	4 heads	LBP, VP, MDF, FF	Shaper sander for different wood species, shapes and sands. Edges w/2 counter rotating sanders; jump cope w/2 shapers to eliminate blow out; foil-edge finishing to run MDF opt.
A117	5, 13		■	Variable	6	LBP, VP, MDF, FF	High-speed edge shaper sander; quick profile changeover; uses Optisand for hardwoods; 2 shapers for jump cope; 4 sanders for different grits and difficult profiles to sand.
A515 CNC Arch Shaper Sander	5, 13		■	Variable	4	LBP, VP, MDF, FF	Continuously fed rectangular panels can be contoured, shaped and sanded with 2 counter rotating sanders in a single pass. For hardwood raised panel inserts and matching rails.
A525 Arch Shaper Sander	5, 13		■	Variable	4	LBP, VP, MDF, FF	Two floating shapers followed by two counter rotating sanders. Shapes & sands pre-contoured raised panel inserts in a single pass. All stations adjust up & down, tilt 0-45°.
A15 Stile & Rail Shaper	5, 13		■	Variable	1 single or stacked spindle	LBP, VP, MDF, FF	Stile & rail shaper straight cuts inside edges on the stiles, rails & outside edges. Also features an optional space ball inserter.
A26 Cope Shaper	5, 13		■	Auto power	2 single or stacked spindles	LBP, VP, MDF, FF	Coping shaper w/42" long & 16" wide table. PCL clamping for securing the rail ends. Three profile shaper heads can be stacked for quick profile selection.
A1515 CNC Arch Shaper Sander w/Auto Tool Changer & Positioning	5, 13		■	Variable	4 to 6 single or stacked HSK	LBP, VP, MDF, FF	Fully equipped to auto. position adjustments for each setup. Auto tool changer for each shaping/sanding station. Using stacked tooling spindles, each station can access up to 15 tools plus remember up to 100 patterns. Shape & sand arched panels w/o precontouring.
Hans Weber Corp., P.O. Box 3387, Olathe, KS 66063 Tel: (913) 254-1611 Fax: (913) 254-1582							
Basic	2	■		3000 sfpm	1 or 2	VP, P, FF, O	Drum or drum/combi, solid wood, 75" long belt (43"/50").
LCS Series	2	■		3400 sfpm	1 or 2	VP, P, FF, O	Drums/segmented pads (patented ISA system), 75" long belt (43"/53").
LCE Series	2	■	■	3400 sfpm	1, 2 or 3	VP, P, FF, O	Same plus 85" belts, constant pass line, sealer sanding (43"/53"). Cross & CBF.
KSF Series	1, 2, 12		■	4000 sfpm	1-4	VP, P, FF, O	Same plus 85" or 103" belts, CBF & cross belt heads knife planer, top/bottom (43"/53"/63").
KSV Series	1, 2, 12		■	4400 sfpm	1-10	VP, P, FF, O	Same plus 24/7 operation (43"/53"/63"/75"/88").
M-DK	1, 2, 12		■	9000 sfpm	any	LBP, VP, P, FF, O, W	Panel sander, 24" to 126", opposed heads, high production.
M	1, 2, 10, 12	■	■	any	any	LBP, VP, P, FF, O, W	Custom, up to 126".
APPLICATION: LBP = Lumber & Basic Products VP = Veneer & Plywood P = Particleboard FF = Furniture & Fixtures O = Other W = Waferboard							
TYPE CODE: Numbers in "Type" column are keyed to use descriptions below							
1. Abrasive Planer 3. Drum 5. Edge Sander 7. Open Drum 9. Spool 11. Disc 13. Profile/Custom Sanding							
2. Widebelt 4. Stroke Type 6. Pneumatic Drum 8. Vertical Belt 10. Brush 12. Other 14. Sander for Curved/Irregular Pieces							